

Type Checking in Cool I

Adapted from Lectures by
Profs. Alex Aiken and George Necula (UCB)

Outline

- Type concepts in COOL
- Notation for type rules
 - Logical rules of inference
- COOL type rules
- General properties of type systems

Cool Types

- The types are:
 - Class Names
 - SELF_TYPE
- The user declares types for identifiers
- The compiler infers types for expressions
- **Type Checking** is the process of verifying fully typed programs
- **Type Inference** is the process of filling in missing type information
 - The two are different, but are often used interchangeably

Rules of Inference

- We have seen two examples of formal notation specifying parts of a compiler
 - Regular expressions
 - Context-free grammars
- The appropriate formalism for type checking is logical rules of inference
If E_1 and E_2 have certain types, then E_3 has a certain type

From English to an Inference Rule

- The notation is easy to read with practice
- Start with a simplified system and gradually add features
- Building blocks
 - Symbol $\wedge$ is "and"
 - Symbol $\Rightarrow$ is "if-then"
 - $x:T$ is " x has type T "

From English to an Inference Rule (2)

If e_1 has type `Int` and e_2 has type `Int`,
then $e_1 + e_2$ has type `Int`

$(e_1 \text{ has type } \text{Int} \wedge e_2 \text{ has type } \text{Int}) \Rightarrow$
 $e_1 + e_2 \text{ has type } \text{Int}$

$(e_1: \text{Int} \wedge e_2: \text{Int}) \Rightarrow e_1 + e_2: \text{Int}$

From English to an Inference Rule (3)

The statement

$$(e_1 : \text{Int} \wedge e_2 : \text{Int}) \Rightarrow e_1 + e_2 : \text{Int}$$

is a special case of

$$\text{Hypothesis}_1 \wedge \dots \wedge \text{Hypothesis}_n \Rightarrow \text{Conclusion}$$

This is an inference rule

Notation for Inference Rules

- By tradition inference rules are written

$$\frac{\boxed{\text{Hypothesis}_1} \dots \boxed{\text{Hypothesis}_n}}{\boxed{\text{Conclusion}}}$$

- Cool type rules have hypotheses and conclusions

$$\boxed{e:T}$$

- $\boxed{}$ means "it is provable that ..."

Two Rules

$$\frac{i \text{ is an integer}}{\boxed{i : \text{int}}} \quad [\text{Int}]$$

$$\frac{\boxed{e_1 : \text{int}} \quad \boxed{e_2 : \text{int}}}{\boxed{e_1 + e_2 : \text{int}}} \quad [\text{Add}]$$

Two Rules (Cont.)

- These rules give templates describing how to type integers and + expressions
- By filling in the templates, we can produce complete typings for expressions

$$\frac{\frac{1 \text{ is an integer}}{\boxed{1 : \text{Int}}} \quad \frac{2 \text{ is an integer}}{\boxed{2 : \text{Int}}}}{\boxed{1+2 : \text{Int}}}$$

Soundness

- A type system is *sound* if
 - Whenever $\boxed{e:T}$
 - Then e evaluates to a value of type T
- We only want sound rules.

$$\frac{i \text{ is an integer}}{\boxed{i:\text{Object}}}$$

Type Checking Proofs

- Type checking proves facts $e: T$
 - Proof is on the structure of the AST
 - Proof has the shape of the AST
 - One type rule is used for each AST node
- In the type rule used for a node e :
 - Hypotheses are the proofs of types of e 's sub-expressions
 - Conclusion is the type of e
- Types are computed in a *bottom-up* pass over the AST

Rules for Constants

$\frac{}{\Box \text{ false: Bool}}$ [Bool]

$\frac{s \text{ is a string constant}}{\Box s: \text{String}}$ [String]

Rule for New

`new T` produces an object of type `T`
- Ignore `SELF_TYPE` for now ...

$\frac{}{\Box \text{ new } T: T}$ [New]

Two More Rules

$\frac{\Box e: \text{Bool}}{\Box \neg e: \text{Bool}}$ [Not]

$\frac{\Box e_1: \text{Bool} \quad \Box e_2: T}{\Box \text{ while } e_1 \text{ loop } e_2 \text{ pool: Object}}$ [Loop]

A Problem

- What is the type of a variable reference?

$\frac{x \text{ is an identifier}}{\Box x: ?}$ [Var]

- The local, structural rule does not carry enough information to give `x` a type.

A Solution

- Put more information in the rules!
- A *type environment* gives types for *free* variables
 - A type environment is a function from `ObjectIdentifiers` to `Types`
 - A variable is *free* in an expression if it is not defined within the expression

Type Environments

Let `O` be a function from `ObjectIdentifiers` to `Types`

The sentence

$O \Box e: T$

is read: Under the assumption that variables have the types given by `O`, it is provable that the expression `e` has the type `T`

Modified Rules

The type environment is added to the earlier rules:

$$\frac{i \text{ is an integer}}{O \sqcup i: \text{int}} \quad [\text{Int}]$$

$$\frac{\begin{array}{l} O \sqcup e_1: \text{int} \\ O \sqcup e_2: \text{int} \end{array}}{O \sqcup e_1 + e_2: \text{int}} \quad [\text{Add}]$$

New Rules

And we can write new rules:

$$\frac{O(x) = T}{O \sqcup x: T} \quad [\text{Var}]$$

Let

$$\frac{O[T_0/x] \sqcup e_1: T_1}{O \sqcup \text{let } x: T_0 \text{ in } e_1: T_1} \quad [\text{Let-No-Init}]$$

$O[T/y]$ means O modified to return T on argument y

Note that the **let** rule enforces variable scope

Notes

- The type environment gives types to the free identifiers in the current scope
- The type environment is *passed down* the AST from the root towards the leaves
- Types are *computed up* the AST from the leaves towards the root

Let with Initialization

Now consider **let** with initialization:

$$\frac{\begin{array}{l} O \sqcup e_0: T_0 \\ O[T_0/x] \sqcup e_1: T_1 \end{array}}{O \sqcup \text{let } x: T_0 \leftarrow e_0 \text{ in } e_1: T_1} \quad [\text{Let-Init}]$$

This rule is weak. Why?

Subtyping

- Define a relation $\leq$ on classes
 - $X \leq X$
 - $X \leq Y$ if X inherits from Y
 - $X \leq Z$ if $X \leq Y$ and $Y \leq Z$
- An improvement

$$\frac{\begin{array}{l} O \sqcup e_0: T \\ T \leq T_0 \\ O[T_0/x] \sqcup e_1: T_1 \end{array}}{O \sqcup \text{let } x: T_0 \leftarrow e_0 \text{ in } e_1: T_1} \quad [\text{Let-Init}]$$

Assignment

- Both **let** rules are correct, but more programs typecheck with the second one
- More uses of subtyping:

$$\frac{O(\text{Id}) = T_0 \quad O \sqsubseteq e_1 : T_1 \quad T_1 \leq T_0}{O \sqsubseteq \text{Id} \leftarrow e_1 : T_1} \text{ [Assign]}$$

Initialized Attributes

- Let $O_C(x) = T$ for all attributes $x:T$ in class C
- Attribute initialization is similar to **let**, except for the scope of names

$$\frac{O_C(\text{Id}) = T_0 \quad O_C \sqsubseteq e_1 : T_1 \quad T_1 \leq T_0}{O_C \sqsubseteq \text{Id} : T_0 \leftarrow e_1 : T_1} \text{ [Attr-Init]}$$

If Then Else

- Consider:
if e_0 then e_1 else e_2 fi
- The result can be either e_1 or e_2
- The type is either e_1 's type or e_2 's type
- The best we can do is the smallest supertype larger than the type of e_1 or e_2

Least Upper Bounds

- $\text{lub}(X,Y)$, the least upper bound of X and Y , is Z if
 - $X \leq Z \wedge Y \leq Z$
 Z is an upper bound
 - $X \leq Z' \wedge Y \leq Z' \Rightarrow Z \leq Z'$
 Z is least among upper bounds
- Digression (Examples with ordered sets)**
 - Least common multiple, Greatest common divisor
 - Set Union, Set Intersection
 - Maximum, Minimum

If Then Else Revisited

In COOL, the least upper bound of two types is their least common ancestor in the inheritance tree.

$$\frac{O \sqsubseteq e_1 : \text{Bool} \quad O \sqsubseteq e_2 : T_2 \quad O \sqsubseteq e_3 : T_3}{O \sqsubseteq \text{if } e_1 \text{ then } e_2 \text{ else } e_3 \text{ fi} : \text{lub}(T_2, T_3)} \text{ [If-Then-Else]}$$

Case

- The rule for **case** expressions takes a *lub* over all branches

$$\frac{O \sqsubseteq e_0 : T_0 \quad O[T_1/x_1] \sqsubseteq e_1 : T'_1 \quad \dots \quad O[T_n/x_n] \sqsubseteq e_n : T'_n}{O \sqsubseteq \text{case } e_0 \text{ of } x_1:T_1 \Rightarrow e_1; \dots; x_n:T_n \Rightarrow e_n; \text{ esac} : \text{lub}(T'_1, \dots, T'_n)} \text{ [case]}$$

Method Dispatch

- There is a problem with type checking method calls:

$$\frac{\begin{array}{l} O \sqsubseteq e_0 : T_0 \\ O \sqsubseteq e_1 : T_1 \\ \vdots \\ O \sqsubseteq e_n : T_n \end{array} \quad [\text{Dispatch}]}{O \sqsubseteq e_0.f(e_1, \dots, e_n) : ?}$$

- We need information about the formal parameters and return type of f

CS781(Prasad)

L20TC

31

Notes on Dispatch

- In Cool, method and object identifiers live in different name spaces
 - A method `foo` and an object `foo` can coexist in the same scope
- In the type rules, this is reflected by a separate mapping M for method signatures

$$M(C, f) = (T_1, \dots, T_n, T_{n+1})$$
 means in class C there is a method f

$$f(x_1 : T_1, \dots, x_n : T_n) : T_{n+1}$$

CS781(Prasad)

L20TC

32

The Dispatch Rule Revisited

$$\frac{\begin{array}{l} O, M \sqsubseteq e_0 : T_0 \\ O, M \sqsubseteq e_1 : T_1 \\ \vdots \\ O, M \sqsubseteq e_n : T_n \\ M(T_0, f) = (T'_1, \dots, T'_n, T'_{n+1}) \\ T_i \leq T'_i \text{ for } 1 \leq i \leq n \end{array} \quad [\text{Dispatch}]}{O, M \sqsubseteq e_0.f(e_1, \dots, e_n) : T'_{n+1}}$$

CS781(Prasad)

L20TC

33

Static Dispatch

- Static dispatch is a variation on normal dispatch
- The method is found in the class explicitly named by the programmer
- The inferred type of the dispatch expression must conform to the specified type

CS781(Prasad)

L20TC

34

Static Dispatch (Cont.)

$$\frac{\begin{array}{l} O, M \sqsubseteq e_0 : T_0 \\ O, M \sqsubseteq e_1 : T_1 \\ \vdots \\ O, M \sqsubseteq e_n : T_n \\ T_0 \leq T \end{array} \quad [\text{StaticDispatch}]}{O, M \sqsubseteq e_0.T.f(e_1, \dots, e_n) : T'_{n+1}}$$

CS781(Prasad)

L20TC

35

The Method Environment

- The method environment must be added to all rules
- In most cases, M is passed down but not actually used
 - Only the dispatch rules use M

$$\frac{\begin{array}{l} O, M \sqsubseteq e_1 : \text{int} \\ O, M \sqsubseteq e_2 : \text{int} \end{array} \quad [\text{Add}]}{O, M \sqsubseteq e_1 + e_2 : \text{int}}$$

CS781(Prasad)

L20TC

36

More Environments

- For some cases involving **SELF_TYPE**, we need to know the class in which an expression appears
- The full type environment for COOL:
 - A mapping O giving types to object id's
 - A mapping M giving types to methods
 - The current class C

Sentences

The form of a *sentence* in the logic is

$$O, M, C \sqsubseteq e : T$$

Example:

$$\begin{array}{l} O, M, C \sqsubseteq e_1 : \text{int} \\ O, M, C \sqsubseteq e_2 : \text{int} \\ \hline O, M, C \sqsubseteq e_1 + e_2 : \text{int} \end{array} \quad [\text{Add}]$$

Type Systems

- The rules in this lecture are COOL specific
 - More info on rules for **self** next time
 - Other languages have very different rules
- General themes
 - Type rules are defined on the structure of expressions
 - Types of variables are modeled by an environment
- Warning: Type rules are very compact!

One Pass Type Checking

- COOL type checking can be implemented in a single traversal over the AST
- Type environment is passed down the tree
 - From parent to child
- Types are passed up the tree
 - From child to parent

Implementing Type Systems

$$\begin{array}{l} O, M, C \sqsubseteq e_1 : \text{int} \\ O, M, C \sqsubseteq e_2 : \text{int} \\ \hline O, M, C \sqsubseteq e_1 + e_2 : \text{int} \end{array} \quad [\text{Add}]$$

```
TypeCheck(Environment, e1 + e2) = {  
  T1 = TypeCheck(Environment, e1);  
  T2 = TypeCheck(Environment, e2);  
  Check T1 == T2 == Int;  
  return Int; }
```

Soundness : Java Digression

Kinds of Conversion

- Identity Conversions
- String Conversions
- Widening Primitive Conversions (19)
 - $\text{byte} \Rightarrow \text{short} \Rightarrow \text{int} \Rightarrow \text{long} \Rightarrow \text{float} \Rightarrow \text{double}$
 - $\text{char} \Rightarrow \text{int} \Rightarrow \text{long} \Rightarrow \text{float} \Rightarrow \text{double}$
 - $\text{int} \Rightarrow \text{float}$ may lose precision
- Narrowing Primitive Conversions (19+4)
 - $\text{char} \Rightarrow \text{short}$, $\text{char} \Rightarrow \text{byte}$,
 - $\text{byte} \Rightarrow \text{char}$, $\text{short} \Rightarrow \text{char}$
 - may lose sign and magnitude information

• Widening Reference Conversions

- $\text{null type} \Rightarrow \text{any reference type}$
- $\text{any reference type} \Rightarrow \text{class Object}$
- $\text{class } S \Rightarrow \text{class } T$, if $S \text{ extends } T$
- $\text{class } S \Rightarrow \text{interface } K$, if $S \text{ implements } K$
- $\text{interface } J \Rightarrow \text{interface } K$, if $J \text{ extends } K$
- $\text{array } SC[] \Rightarrow \text{array } TC[]$, if $SC \Rightarrow TC$, and both SC and TC are reference types.
- $\text{array } T \Rightarrow \text{interface Cloneable}$
- $\text{array } T \Rightarrow \text{interface Serializable}$

• Narrowing Reference Conversions

- Permitted among reference types that can *potentially share common instances*.
- These conversions require *run-time test* to determine if the actual reference is a legitimate value of the new type.
 - Observe the interpretation of *final class*.
 - Observe that every *non-final class* can potentially be *extended to implement an interface*.

Narrowing Reference Conversions

- $\text{class Object} \Rightarrow \text{any reference type}$
- $\text{class } S \Rightarrow \text{class } T$, if $T \text{ extends } S$
- $\text{class } S \Rightarrow \text{interface } K$, if S is not *final* and S does not *implement* K
- $\text{interface } K \Rightarrow \text{class } T$, if T is not *final*
- $\text{interface } K \Rightarrow \text{class } T$, if T is *final* and $T \text{ implements } K$
- $\text{interface } J \Rightarrow \text{interface } K$, if K does not *extend* J and there is no common method with same signature but different return types.
- $\text{array } SC[] \Rightarrow \text{array } TC[]$, if $SC \Rightarrow TC$, and both SC and TC are reference types.

Motivation for Primitive Array Type Constraints

```
int i = 10;
long l = i;
byte b = (byte) i;
int[] iA = new int[5];
long[] lA = (long[]) iA; //error
lA[2] = l;                // reason
byte[] bA = (byte[]) iA; // error
b = bA[2];               // reason
```

Motivation for Reference Array Type Constraints

```
Point i = new Point();
Object l = i;
ColoredPoint b = (ColoredPoint) i;
// throws exception
Point[] iA = new Point[5];
Object[] lA = (Object[]) iA;
lA[2] = l;                // no exception
b = lA[2];                // *error*
l = lA[2];
ColoredPoint[] bA = (ColoredPoint[]) iA;
// throws exception
```

Another Example: Primitive Array Type

```
void f(int[] a) {
    int i = a[0];
    a[0] = i;
}
```


```
long[] la = new long[8];
short[] sa = new short[8];
f(la); // banned : compile-time error
f(sa); // banned : compile-time error
```

Another Example: Reference Array Type

```
void f(Point[] pa) {
    pa[0] = new Point();
}
```

```
Object[] oa = new Object[8];
f(oa); // compile-time error
f((Point []) oa); // throws ClassCastException
ColoredPoint[] cpa =
    new ColoredPoint[8];
f(cpa); // array store exception in f
```

class S $\Rightarrow$ *interface K*



```
class S;
interface K;
class C extends+ S
    implements+ K;
```

```
C c = new C();
S s = c;
K k = (C) s;
s = (C) k;
```